

GVCTX-1 Series

From 0.4 μH to 302.5 μH



SPECIFICATIONS

Parts are available in $\pm 20\%$ tolerance only.

Part Number	PARALLEL			SERIES		
	OCL ($\mu\text{H}\pm 20\%$)	DCR Max. (Ω)	Full Load Current (A dc)	OCL ($\mu\text{H}\pm 20\%$)	DCR Max. (Ω)	Full Load Current (A dc)
GVCTX0.47-1	0.40	0.005	5.50	1.60	0.020	2.75
GVCTX0.68-1	0.63	0.006	4.50	2.50	0.024	2.25
GVCTX1-1	0.90	0.007	4.20	3.60	0.028	2.10
GVCTX2-1	2.03	0.010	4.10	8.10	0.040	2.05
GVCTX5-1	4.90	0.030	2.30	19.60	0.122	1.15
GVCTX8-1	8.10	0.039	2.00	32.40	0.157	1.00
GVCTX10-1	10.00	0.044	1.90	40.00	0.176	0.95
GVCTX15-1	14.40	0.080	1.10	57.60	0.319	0.55
GVCTX20-1	19.60	0.146	1.00	78.40	0.583	0.50
GVCTX25-1	25.60	0.167	0.74	102.40	0.668	0.37
GVCTX33-1	32.40	0.293	0.72	129.60	1.171	0.36
GVCTX50-1	50.63	0.365	0.64	202.50	1.461	0.32
GVCTX68-1	67.60	0.516	0.54	270.40	2.064	0.27
GVCTX100-1	99.23	0.784	0.44	396.90	3.137	0.22
GVCTX150-1	148.23	0.965	0.38	592.90	3.861	0.19
GVCTX200-1	202.50	1.142	0.37	810.00	4.567	0.19
GVCTX300-1	302.50	1.431	0.22	1210.00	5.724	0.11

PHYSICAL DIMENSIONS

Size	A	B	C	D	E	F
	Nom.	Nom.	Max.	Max.	Max.	Min.
mm	9.0	11.4	5.12	3.05	3.56	0.762
inches	0.35	0.45	0.20	0.12	0.14	0.03

CHARACTERISTICS

Description: SMD 4 Pads Inductors

Applications: Single inductors, 1:1 coupled inductors, & 1:1 isolation transformers

Operating Temperature: -40°C to $+85^{\circ}\text{C}$

Storage Temperature: -40°C to $+125^{\circ}\text{C}$

Inductance Tolerance: $\pm 20\%$

Testing: Inductance is tested on an HP4285A at 100 kHz

Packaging: Bulk pack; packaged in plastic trays

Marking: Parts marked with inductance code & series type

Additional Information: Additional electrical & physical information available upon request

Samples available. See website for ordering information.

CONNECTION DIAGRAM

